



PCT/GB 00 / 01029


20



2000

INVESTOR IN PEOPLE

GB 00 / 1029



The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 30 MAR 2000

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Patent  
Rule 16)The  
Patent  
Office

1/77

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office  
Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference	38.46.68343		
2. Patent application number (The Patent Office will fill in this part)	9906477.6		
3. Full name, address and postcode of the or of each applicant ( <i>underline all surnames</i> )	PyroSequencing AB Vallongatan 1 S-752 28 Uppsala Sweden		
Patents ADP number ( <i>if you know it</i> )	7459605001		
If the applicant is a corporate body, give country/state of incorporation	Sweden		
4. Title of the invention	Liquid dispensing apparatus		
5. Name of your agent ( <i>if you have one</i> )	Frank B. Dehn & Co.		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	179 Queen Victoria Street London EC4V 4EL		
Patents ADP number ( <i>if you know it</i> )	166001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and ( <i>if you know it</i> ) the or each application number	Country	Priority application number ( <i>if you know it</i> )	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	Yes		

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form -

Description 9

Claim(s) -

Abstract -

Drawing(s) 1 + 1

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) -

Request for substantive examination (Patents Form 10/77) -

Any other documents (please specify) -

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date 19 March 1999

12. Name and daytime telephone number of person to contact in the United Kingdom

A.J. Piésold  
0171 206 0600

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s) of the form. Any continuation sheet should be attached to this form.
- If you have answered 'Yes', Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

68343.604

Liquid Dispensing Apparatus

5 This invention relates to liquid dispensing  
apparatus and in particular to liquid dispensing  
apparatus which are able to dispense small volumes of  
liquid.

10 In certain applications it is desirable to be able  
to dispense very small volumes of liquid from a  
container, for example in the range 50-500 nanolitres  
(nl). Drops of this size cannot normally be produced by  
pumping liquid out of a capillary since surface tension  
will hold the drop to the tip of the capillary until it  
is sufficiently large that its weight overcomes this  
15 surface tension. This does not happen until the volume  
of the drop is of the order of 10 to 50 microlitres -  
i.e. 2 to 3 orders of magnitude greater than the range  
of interest.

20 Devices are available which overcome this  
limitation by forcing a measured amount of liquid  
through the tip of a nozzle using a piezo-electric  
actuator acting on the liquid. However such systems are  
expensive and may only be used with a single type of  
liquid at a time - thus multiplying the cost where  
25 several different liquids need to be dispensed.

It is an object of the present invention to provide  
an improved apparatus and when viewed from a first  
aspect the invention provides a liquid dispensing  
apparatus comprising a liquid reservoir, a nozzle and  
30 driving means for forcing liquid through said nozzle,  
said driving means comprising means for generating a  
pulse of gas which impinges upon liquid in the reservoir  
so as to force liquid through the nozzle.

35 Thus it will be seen that in accordance with the  
invention liquid may be dispensed by forcing it through  
the nozzle by means of a pulse of gas. The volume of  
liquid dispensed may be controlled by adjusting the

---

amplitude and duration of the gas pulse. It has been found that this enables accurate control of the volume dispersed, down to the order of 50-500 nl in the preferred embodiment. Furthermore as a gas is used as the medium for transmitting force to the liquid, it is not necessary for any part of the driving means to be in contact with the liquid to be dispensed. This has clear advantages both from the point of view of preventing contamination of the liquid and also the reduced necessity to clean the apparatus.

As the driving impulse is applied to liquid in the reservoir, it is not necessary to have any part of the driving means arranged in the vicinity of the nozzle. This means that the nozzle may be a simple capillary tube and may even be disposable. The nozzle could comprise a separate part removable from the rest of the apparatus. Preferably however the nozzle is an integral part of the apparatus. In a particularly preferred embodiment one or both of the nozzle and the liquid reservoir are moulded from a suitable plastics material, thereby allowing them to be made disposable. More preferably the nozzle and liquid reservoir are both moulded from suitable plastics, most preferably integrally with each other, to form a cartridge. Alternatively such a cartridge or just the nozzle could be made from one or more other suitable materials such as silica or stainless steel.

Cartridges of the kind described above may be provided singly, but preferably a plurality are provided in a cassette. Such an arrangement is novel and advantageous in itself and thus when viewed from a second aspect the present invention provides a cassette comprising a plurality of cartridges for dispensing liquid therefrom, each cartridge comprising a nozzle and a liquid reservoir integrally formed with the nozzle, wherein said nozzle comprises a capillary tube.

---

~~The invention makes it possible, at least in some~~

preferred embodiments, to provide cartridges pre-filled with the necessary liquid and having the required capillary nozzle formed integrally therewith. All that is necessary then is simply to place the liquid  
5 reservoir of the cartridge or each cartridge of a cassette of cartridges in gaseous communication with a means to generate gas pulses, in order to form a liquid dispensing apparatus in accordance with the first aspect of the invention. This is extremely convenient to a  
10 user who thus does not need to be concerned with filling reservoirs with liquid, cleaning the nozzle etc. Indeed in at least preferred embodiments of this aspect of the invention, contact with the liquid to be dispensed may be completely avoided.

15 Alternatively the cartridges may be filled with a suitable liquid prior to use, e.g. a lyophilised reagent which is dissolved in water when required. The preferred embodiments of the invention in which the liquid reservoir is adjacent the nozzle are advantageous  
20 in this context since just the required amount of reagent can be made up as required without extra being required to accommodate dead space in pipes etc.

Cassettes of cartridges in accordance with the invention as described above are useful in many  
25 applications including but not limited to immuno assays, cell assay, drug screening and they are particularly useful for sequencing DNA using the method often referred to as "Sequencing By Synthesis" as they allow for example a cassette having cartridges containing each  
30 of the four nucleotides required for DNA sequencing. Preferably therefore the cartridges respectively contain one or more nucleotides. The ability to provide a plurality of cartridges in a single cassette further allows a complete set of reagents required for a  
35 sequencing programme to be provided. Thus preferably further cartridges of the cassette respectively contain one or more enzymes, more preferably selected from a

---

group comprising polymerase, luciferase, adenosine triphosphate (ATP) sulfurylase, and a nucleotide-degrading enzyme such as apyrase. Such a set of reagents is particularly useful for the method of genetic sequencing set out in WO 98/13523. Indeed it will be appreciated that the invention extends to a method of genetic sequencing using a liquid dispensing apparatus as herein described.

As discussed above, cartridges of the kind described above may be filled by a user with the appropriate liquid as required. Alternatively the cartridge or each cartridge of a cassette is pre-filled with the appropriate liquid and sealed, the seal being broken upon mounting the cartridge into an apparatus which includes the gas pulse generation means. Preferably the seal is broken by the action of mounting the cartridge into the apparatus. Advantageously a conduit for establishing gaseous communication with the interior of the liquid reservoir of the cartridge breaks the seal.

It will be seen from the above that a sealed cartridge containing a liquid to be dispensed by means of apparatus in accordance with the first aspect of the invention is in itself not only novel, but particularly convenient for a user and thus when viewed from a further aspect the present invention provides a cartridge comprising a liquid reservoir having a predetermined liquid received therein, said reservoir being closed at one end thereof by frangible sealing means, and a nozzle attached to or integrally formed with said reservoir and in fluid communication therewith.

As an alternative it will be seen that the invention extends to a cartridge for use in a liquid dispensing apparatus as hereinbefore described comprising a liquid reservoir, and a nozzle attached to or integrally formed with said reservoir and in fluid

---

communication therewith, in combination with a reagent, preferably a nucleotide or enzyme.

5 The reagent e.g. nucleotide or enzyme could be in a suitable liquid form or could be lyophilised. In the latter case a readily available diluent such as water could be used, or a suitable diluent could instead also be provided as part of the combination.

10 The frangible sealing means preferably comprises a foil membrane e.g. of aluminium covering an opening onto the reservoir. This is a cost-effective way of retaining liquid in the reservoir without it becoming contaminated, whilst at the same time being relatively easy to pierce - e.g. by a gas nozzle associated with the gas pulse generation means.

15 The predetermined liquid preferably comprises a nucleotide or an enzyme.

Where an enzyme is provided, either as the predetermined liquid in a pre-filled cartridge or as a separate reagent to be added by a user, the enzyme is preferably selected from a group comprising polymerase, luciferase, adenosine triphosphate (ATP) sulfurylase, and a nucleotide-degrading enzyme such as apyrase.

20 The bore of the nozzle or nozzles is preferably within the range 0.05 to 0.2 mm, most preferably about 0.1 mm. The length of the nozzle is preferably in the range 1 to 15 mm, most preferably 5 mm.

30 The means for generating the gas pulses may comprise any suitable means - e.g. a bellows arranged to undergo a rapid reduction in volume. Preferably however the pulse generation means comprises a source of pressurised gas which may be selectively placed into communication with the liquid reservoir. Such arrangements are especially beneficial since a single source of pressurised gas may be used to drive a plurality of liquid reservoirs, thereby giving a significant saving in cost over arrangements where driving means are individually provided for each of a

---



number of nozzles. Means for selectively placing the liquid reservoir into communication with the source of gas may be provided for each of such liquid reservoirs or two or more of them may be associated with a single selection means so that their contents are dispensed simultaneously.

Preferably one or more valves is provided to effect said selective communication and in the preferred embodiment an electromagnetic valve is used. This is particularly advantageous since electromagnetic valves can be operated very quickly and accurately with little mechanical wear.

Where, as is preferred, the apparatus for dispensing liquid comprises gas pulse generation means in the form of means for selectively communicating a source of pressurised gas with the liquid reservoir, the source of pressurised gas may be comprised within the apparatus. Most preferably the source of pressurised gas comprises a compressor supplying a pressure reservoir. Alternatively, the apparatus may comprise a gas inlet for connection to an external source of pressurised gas. In either case the apparatus of the invention preferably comprises means to regulate the pressure of the incoming gas thereby allowing the amplitude of the pulses generated to be accurately controlled and thus the volume of liquid to be accurately controlled as a consequence. The pressure regulation means may comprise a mechanical release valve or the like. Preferably however such means comprises an electronic pressure sensor which is used to monitor the pressure in the reservoir or gas inlet and means for increasing or decreasing said pressure in response to the signal from the pressure sensor to maintain the pressure within a predetermined range.

The gas pulse generation means preferably generates pressure pulses having an amplitude in the range 200 to 1000 millibars, with a pulse width in the range 1-1000

---

milliseconds. This enables volumes in the range 50 nl to 10000 nl (10 $\mu$ l) to be dispensed.

A preferred embodiment of the present invention will now be described, by way of example only, with  
5 reference to the accompanying Figure which is a schematic view of a cassette of cartridges and liquid dispensing apparatus in accordance with the invention.

Turning to the Figure there may be seen a liquid dispensing apparatus comprising a cartridge cassette  
10 designated generally by the reference numeral 1. This cassette contains eight cartridges 2, three of which are visible in the drawing. Each cartridge 2 is partly filled with a reagent used for genetic sequencing. The volume of the cartridges is approximately 2 ml.  
15 Different reagents are provided in each cartridge 2. Specifically, four of the cartridges 2 contain the deoxynucleotide triphosphate of one each of the four bases cytosine, guanine, adenosine and thymine. Four further cartridges 2 contain polymerase, luciferase,  
20 apyrase and ATP sulfurylase. Equally however some or all of the cartridges could have the same contents.

At the end of each cartridge 2 there is a capillary nozzle 6. This nozzle has a bore of 0.1 mm. In the  
25 depicted embodiment the nozzle 6 is integrally moulded with the rest of the cartridge 2 from a polymer. However the cartridge could be formed with means to receive a separate nozzle.

The cassette 1 has an outer case 8 which protects the cartridges 2 from contamination by the user handling  
30 them and conversely protects the user from having to come into contact with the liquid being dispensed or the very fine, i.e. sharp nozzles 6. Apertures 10 are provided in the base of the cassette casing 8 which are aligned with the nozzles 6 to allow the liquid through.

35 At the upper end of the cassette 1 a thin metal foil 16 is provided over the tops of the cartridges 2 to seal them. The foil 16 extends across the open upper

---

end of the cassette 1 formed by the side walls of the casing 8, but slightly downwardly set from the top edge so as to leave an upstanding lip around the top of the foil 16.

5       The cassette 1 is installed in a carriage 18 which can be moved laterally in both directions over a Micro Titre Plate (MTP) 12. The MTP has 96 wells 14, three of which are shown. The cassette 1 is actually received in a downwardly tapering chamber 20, so as to rest on an  
10       apertured plate 22, the apertures of which are in alignment with the apertures 10 in the cassette and, when the carriage 18 is properly positioned, also with the wells 14 of the MTP 12.

15       The cassette 1 is retained in the chamber 20 by means of a hinged lid 3, having a rubber seal 24 on its underside which is a tight fit inside the lip at the top edge of cassette casing 8. The seal 24 is arranged also to ensure that the cartridges 2 are sealed with respect to one another as well as with respect to the lid 3.

20       Mounted in the lid 3 is an array of punching cannulae 28, one for each of the cartridges 2. These cannulae 28 have sharp tips and so as the lid 3 is hinged downwardly onto the cassette 1 in the chamber 20, the cannulae 28 pierce the foil seal 28. The other ends  
25       of the cannulae are each connected by means of a pipe 26 to an electromagnetic valve (not shown) which selectively connects the pipe 26 to a source of pressurised gas for a predetermined time to produce a pulse of gas. The pressurised gas is generated by a  
30       compressor type EC Genius/M 202 2305 EU.SV.C which is commercially available from Fini, Zola, Predosa, Bo - Italy.

35       The pulse of gas forces a measured amount of reagent 4 out of the cartridge 2, through the nozzle 6 and into the corresponding well 14 on the MTP 12. A 500 millibar pulse, for 10 milliseconds dispenses approximately 200 nanolitres of reagent into the well

---

14. Reagent is only dispensed from one of the  
cartridges 2 at a time although simultaneous dispensing  
is also possible and this could be useful e.g. where a  
plate having a greater number of wells was used with an  
5 interleaved series of wells used so that dispensing into  
the wells of several distinct series can be carried out  
without moving the carriage 18.

Once the reagents in the cartridges have been used,  
the cassette may simply be removed by opening the lid 3  
10 and replaced with a new one, the fresh seals being  
broken by the cannulae 28. Since neither the cannulae  
28 nor any other permanent part of the apparatus comes  
into contact with the reagents at any stage, there is  
little chance of contamination and it is not necessary  
15 to clean the apparatus between uses, even if different  
reagents are being used.

Although an embodiment of the invention which has a  
cassette comprising several cartridges has been  
described, it will be understood by those skilled in the  
20 art that the invention is not limited to using several  
cartridges and that a single cartridge reservoir could  
be used instead. Furthermore, the liquid reservoir need  
not be removable and could instead be an integral part  
of the apparatus.

25




Fig.